

## 20' Skagit Windshield Inboard Performance Bulletin



### Performance Data

RPM	MPH	GPH	MPG
1000	00.00	00.00	00.00
1500	00.00	00.00	00.00
2000	00.00	00.00	00.00
2500	<b>18.00</b>	<b>05.50</b>	<b>03.20</b>
3000	<b>33.00</b>	<b>08.60</b>	<b>03.80</b>
3500	<b>41.00</b>	<b>12.90</b>	<b>03.10</b>
4000	<b>47.00</b>	<b>18.90</b>	<b>02.40</b>
4170 WOT	<b>49.00</b>	<b>23.60</b>	<b>02.00</b>
5000	00.00	00.00	00.00
5500	00.00	00.00	00.00
6000	00.00	00.00	00.00
6500	00.00	00.00	00.00

° Data may vary due to changes in the weather, elevation, options, equipment, load and boat bottom configuration.

° Speed Data was gathered using a GPS reciever, and averaged from two runs in opposite directions.

° This boat was equipped with a stomp grate, which slows boat approximately 2-3 MPH.

### Boat Specifications

#### Wooldridge 20' Skagit Inboard

Length (LOA)	20'3"
Beam	93"
Weight as Tested	2775lbs
Maximum Horsepower	N/A
Fuel Capacity	50gal.

#### Engine: KEM 5.3L V8 VVT DI

Horsepower	343
Fuel Induction	EFI
Displacment	5.3L
Weight	707 lbs

#### Jet & Impeller

Model	Hamilton 212
Diameter/Pitch	2.9

#### Test Conditions

Number of Persons	2
Payload	620
Air Temperature	80
Water Temperature	74
Elevation	20
Wind Velocity	0

**Wooldridge**  
Est. 1915

(206) 722-8998  
info@wooldridgeboats.com  
www.wooldridgeboats.com

Factory / Showroom  
1303 S 96th. St.  
Seattle, WA 98108-5011